

DETARMAX AA

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : DETARMAX AA

Product code : 304303/304313

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name : IPC S.A.S..

Address : 10, Quai Commandant Malbert - CS 71821.29218.BREST Cedex 1.France.

Telephone : +33 (0)2 98 43 45 44. Fax : +33 (0)2 98 44 22 53.

ipc@groupe-ipc.com

http://www.ipc-sa.com

1.4. Emergency telephone number : +33 (0)2.98.43.45.44.

Association/Organisation : .

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :

DANGER

Additional labeling :

EUH208

Contains METHENAMINE. May produce an allergic reaction.

Hazard statements :

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

Precautionary statements - Prevention :

P264

Wash thoroughly after handling.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

DETARMAX AA

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor/...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 017_002_01_X CAS: 7647-01-0 EC: 231-595-7 REACH: 01-2119484862-27-XXXX HYDROCHLORIC ACID	GHS05, GHS07 Dgr Met. Corr. 1, H290 Skin Corr. 1B, H314 STOT SE 3, H335	B [1]	10 \leq x % < 25
INDEX: 603_117_00_0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25-XXXX PROPAN-2-OL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 \leq x % < 2.5
INDEX: 612_101_00_2 CAS: 100-97-0 EC: 202-905-8 REACH: 01-2119474895-20-XXXX METHENAMINE	GHS07, GHS02 Wng Flam. Sol. 2, H228 Skin Sens. 1, H317		0 \leq x % < 2.5

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 017_002_01_X CAS: 7647-01-0 EC: 231-595-7 REACH: 01-2119484862-27-XXXX HYDROCHLORIC ACID	Skin Corr. 1B: H314 C \geq 25% Skin Irrit. 2: H315 10% \leq C < 25% Eye Dam. 1: H318 C \geq 25% Eye Irrit. 2: H319 10% \leq C < 25%	inhalation: ATE = 45.6 mg/l 4h (dust/mist) oral: ATE = 700 mg/kg BW
INDEX: 603_117_00_0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25-XXXX PROPAN-2-OL		dermal: ATE = 13900 mg/kg BW oral: ATE = 5840 mg/kg BW
INDEX: 612_101_00_2 CAS: 100-97-0 EC: 202-905-8 REACH: 01-2119474895-20-XXXX METHENAMINE		oral: ATE = 9200 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

DETARMAX AA

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

DETARMAX AA**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an alkaline decontaminant, such as an aqueous solution of sodium carbonate or similar.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
7647-01-0	8	5	15	10	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA	STEL	Ceiling	Definition	Criteria
7647-01-0			2 ppm	A4	
67-63-0	200 ppm	400 ppm		A4; BEI	

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME	Excess	Notes
7647-01-0		2 ppm 3 mg/m ³	2(I)
67-63-0		200 ppm 500 mg/m ³	2(II)

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

DETARMAX AA

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
7647-01-0	-	-	5	7.6	-	-
67-63-0	-	-	400	980	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7647-01-0	1 ppm 2 mg/m ³	5 ppm 8 mg/m ³			
67-63-0	400 ppm 999 mg/m ³	500 ppm 1250 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

METHENAMINE (CAS: 100-97-0)

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
6.4 mg/kg body weight/day

Dermal contact.
Short term systemic effects.
229 mg/kg body weight/day

Inhalation.
Long term systemic effects.
5.6 mg of substance/m³

Inhalation.
Short term systemic effects.
1400 mg of substance/m³

Consumers.

Ingestion.
Long term systemic effects.
0.8 mg/kg body weight/day

Ingestion.
Short term systemic effects.
20 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
1.9 mg/kg body weight/day

Dermal contact.
Short term systemic effects.
22.9 mg/kg body weight/day

Inhalation.
Long term systemic effects.
1.2 mg of substance/m³

Inhalation.
Short term systemic effects.
140 mg of substance/m³

PROPAN-2-OL (CAS: 67-63-0)

DETARMAX AA**Final use:**

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
888 mg/kg body weight/day

Inhalation.
Long term systemic effects.
500 mg of substance/m3

Consumers.

Ingestion.
Long term systemic effects.
26 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
319 mg/kg body weight/day

Inhalation.
Long term systemic effects.
89 mg of substance/m3

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)**Final use:**

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Long term local effects.
8 mg of substance/m3

Inhalation.
Short term local effects.
15 mg of substance/m3

Predicted no effect concentration (PNEC):**METHENAMINE (CAS: 100-97-0)**

Environmental compartment:
PNEC :

Soil.
0.28 mg/kg

Environmental compartment:
PNEC :

Fresh water.
3 mg/l

Environmental compartment:
PNEC :

Sea water.
0.3 mg/l

Environmental compartment:
PNEC :

Intermittent waste water.
30 mg/l

Environmental compartment:
PNEC :

Fresh water sediment.
2.4 mg/kg

Environmental compartment:
PNEC :

Marine sediment.
0.4 mg/kg

Environmental compartment:
PNEC :

Waste water treatment plant.
100 mg/l

DETARMAX AA**PROPAN-2-OL (CAS: 67-63-0)**

Environmental compartment: PNEC :	Soil. 28 mg/kg
Environmental compartment: PNEC :	Fresh water. 140.9 mg/l
Environmental compartment: PNEC :	Sea water. 140.9 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 140.9 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 552 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 2251 mg/l

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)

Environmental compartment: PNEC :	Fresh water. 0.036 mg/l
Environmental compartment: PNEC :	Sea water. 0.036 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.045 mg/l
Environmental compartment: PNEC :	Marine sediment. 0.045 mg/l
Environmental compartment: PNEC :	Waste water treatment plant. 0.036 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

DETARMAX AA**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- Natural latex

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Suitable type of protective boots :

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Fluid liquid.

Colour

N/A

Odour

Odour threshold : Not stated.

Melting point

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not specified.

DETARMAX AA

Decomposition temperature

Decomposition point/decomposition range : Not specified.

pH

pH : 1.00 +/-1.0.
Strongly acidic.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Dilutable.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : 1.08

Relative vapour density

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

Mixture which by chemical action can corrode and even destroy metals.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

DETARMAX AA**11.1.1. Substances****Acute toxicity :**

METHENAMINE (CAS: 100-97-0)

Oral route :

LD50 = 9200 mg/kg

Species : Rat

Dermal route :

LD50 > 2000 mg/kg

Species : Rat

OECD Guideline 402 (Acute Dermal Toxicity)

PROPAN-2-OL (CAS: 67-63-0)

Oral route :

LD50 = 5840 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 = 13900 mg/kg

Species : Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) :

LC50 > 25 mg/l

Species : Rat

OECD Guideline 403 (Acute Inhalation Toxicity)

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)

Oral route :

LD50 = 700 mg/kg

Species : Rat

Dermal route :

LD50 > 5010 mg/kg

Species : Rabbit

Inhalation route (Dusts/mist) :

LC50 = 45.6 mg/l

Species : Rat

Duration of exposure : 4 h

Respiratory or skin sensitisation :

METHENAMINE (CAS: 100-97-0)

Guinea Pig Maximisation Test (GMPT) :

Sensitiser.

Species : Guinea pig

OECD Guideline 406 (Skin Sensitisation)

PROPAN-2-OL (CAS: 67-63-0)

Local lymph node stimulation test :

Non-Sensitiser.

Species : Guinea pig

OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity :

PROPAN-2-OL (CAS: 67-63-0)

Mutagenesis (in vivo) :

Negative.

Species : Mouse

OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Mutagenesis (in vitro) :

Negative.

Species : Bacteria

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

DETARMAX AA**Carcinogenicity :**

PROPAN-2-OL (CAS: 67-63-0)

Carcinogenicity Test :

Negative.

No carcinogenic effect.

Species : Mouse

OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicant :

PROPAN-2-OL (CAS: 67-63-0)

No toxic effect for reproduction

11.1.2. Mixture**Skin corrosion/skin irritation :**

Corrosive classification is based on an extreme pH value.

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards**SECTION 12 : ECOLOGICAL INFORMATION****12.1. Toxicity****12.1.1. Substances**

METHENAMINE (CAS: 100-97-0)

Fish toxicity :

LC50 = 49800 mg/l

Species : Pimephales promelas

Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 = 36000 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Algae toxicity :

ECr50 3000 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 96 h

NOEC = 1.5 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 14 days

PROPAN-2-OL (CAS: 67-63-0)

Fish toxicity :

LC50 = 9640 mg/l

Species : Pimephales promelas

Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 = 9714 mg/l

Species : Daphnia magna

Duration of exposure : 24 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 > 100 mg/l

Species : Raphidocelis subcapitata

DETARMAX AA

Duration of exposure : 72 h

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)

Fish toxicity :

LC50 = 369 mg/l

Species : Brachydanio rerio

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 213 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances****METHENAMINE (CAS: 100-97-0)**

Biodegradability :

Non-rapidly degradable.

PROPAN-2-OL (CAS: 67-63-0)

Chemical oxygen demand :

DCO = 2.294 g/g

Five-day biochemical oxygen demand :

DBO5 = 1.171 g/g

Biodegradability :

Rapidly degradable.

DBO5/DCO = 0.51

12.3. Bioaccumulative potential**12.3.1. Substances****METHENAMINE (CAS: 100-97-0)**

Octanol/water partition coefficient :

log K_{ow} = -2.18

OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

PROPAN-2-OL (CAS: 67-63-0)

Octanol/water partition coefficient :

log K_{ow} = 0.05

OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

DETARMAX AA

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

3264

14.2. UN proper shipping name

UN3264=CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(hydrochloric acid ...%)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C1	II	8	80	1 L	274	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	8	-	II	1 L	F-A. S-B	274	E2	Category B SW2	SGG1 SG36 SG49

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

- Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): <https://echa.europa.eu/substances-restricted-under-reach>.

- Particular provisions :

No data available.

DETARMAX AA**- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :**

- less than 5 % : non-ionic surfactants

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.