

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Date of issue: 3/15/2018 Revision date: 3/15/2018 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : LOFT AMBIANCE ONE II  
Product code : 10434  
Product identification : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : Deodorant scented atmosphere

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

IPC SAS  
10 QUAI MALBERT - CS 71821 29218 BREST CEDEX 2 - FRANCE  
T 00 33 (0)2-98-43-45-44 - F 00 33 (0)2-98-44-22-53  
[ipc@ipc-sa.com](mailto:ipc@ipc-sa.com) - [www.ipc-sa.com](http://www.ipc-sa.com)

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Aerosol 1 H222;H229  
Aquatic Chronic 3 H412  
Full text of hazard classes and H-statements : see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P260 - Do not breathe spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P403 - Store in a well-ventilated place.  
P273 - Avoid release to the environment.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

EUH-statements :

EUH208 - Contains Iso E super 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one(54464-57-2), (32210-23-4), ACETYL CEDRENE(32388-55-9), 1-(2,6,6-TRIMETHYL-1,3-CYCLOHEXADIEN-1-YL)-2-BUTEN-1-ONE (BETA-DAMASCENONE)(23696-85-7). May produce an allergic reaction.

Extra phrases :

Not to be used for any purpose other than the one the product was designed for.  
For professional use only.

#### 2.3. Other hazards

No additional information available

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-Butane (contenant <0.1% butadiène)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	60 - 80	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	20 - 30	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	2 - 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Iso E super 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one	(CAS-No.) 54464-57-2 (EC-No.) 259-174-3 (REACH-no) 01-2119489989-04	0.5 - 1	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
	(CAS-No.) 32210-23-4 (EC-No.) 250-954-9	0.1 - 0.5	Skin Sens. 1B, H317
ACETYL CEDRENE	(CAS-No.) 32388-55-9 (EC-No.) 251-020-3	0.1 - 0.5	Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Galaxolide 50 DEP (1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran	(CAS-No.) 1222-05-5 (EC-No.) 214-946-9 (REACH-no) 01-2119488227-29	0.1 - 0.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Alpha-cedrene	(CAS-No.) 469-61-4 (EC-No.) 207-418-4	< 0.1	Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
1-(2,6,6-TRIMETHYL-1,3-CYCLOHEXADIEN-1-YL)-2-BUTEN-1-ONE (BETA-DAMASCENONE)	(CAS-No.) 23696-85-7 (EC-No.) 245-833-2	< 0.1	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	(C >= 50) Eye Irrit. 2, H319

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Wash with plenty of water/....
First-aid measures after eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Allow the victim to rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Ingestion unlikely.

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.3. Indication of any immediate medical attention and special treatment needed

Advice to physicians: Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Alcohol resistant foam. Dry powder.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Reactivity in case of fire : Prevent fire fighting water from entering the environment.

### 5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.  
Firefighting instructions : Exercise caution when fighting any chemical fire. During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Remove ignition sources. Ventilate area. Do not smoke. Provide local exhaust or general room ventilation. Evacuate and limit access.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Do not touch spilled material. Evacuate area.

#### 6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. Provide adequate ventilation. Remove all sources of ignition. Avoid contact with skin and eyes. Do not inhale vapour.

### 6.2. Environmental precautions

Notify authorities if liquid enters sewers or public waters. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean spills promptly. Collect the residue by means of a non-combustible absorbent material. Waste mixtures containing butane / propane must not enter drains or sewers where vapors could accumulate and ignite.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Good ventilation of the workplace required. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck. During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol. Do not spray tha aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in runing, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep at temperature not exceeding 50 °C. Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.

Storage conditions : Recommendations applicable to warehouses and reserves which are stored aerosols. It is recommended to de-normalize aerosols in stock . The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock . Do not smoke.

To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).

It is recommended :

- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames

- To use the procedure of fire when working . Store in a dry, well ventilated place .

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7.3. Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### N-Butane (contenant <0.1% butadiène) (106-97-8)

France	Local name	n-Butane
France	VME (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
France	VME (ppm)	800 ppm
France	Note (FR)	Valeurs recommandées/admises

#### Ethanol (64-17-5)

France	Local name	Alcool éthylique
France	VME (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
France	VME (ppm)	1000 ppm
France	VLE (mg/m <sup>3</sup> )	9500 mg/m <sup>3</sup>
France	VLE (ppm)	5000 ppm
France	Note (FR)	Valeurs recommandées/admises

### 8.2. Exposure controls

#### Hand protection:

None under normal conditions

#### Eye protection:

No special eye protection equipment recommended under normal conditions of use

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

#### Other information:

Do not eat, drink or smoke during use. Provide local exhaust or general room ventilation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: perfumed.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.87 (PA)
Solubility	: No data available
Log Pow	: No data available

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions. Extremely flammable aerosol. Heating may cause a fire or explosion.

### 10.3. Possibility of hazardous reactions

None under normal conditions.

### 10.4. Conditions to avoid

Heat. Open flame. Direct sunlight. Sparks. Avoid contact with hot surfaces. Remove all sources of ignition.

### 10.5. Incompatible materials

Aerosol cases in metal, do not bring into contact with oxidize, acids or basis. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

### N-Butane (contenant <0.1% butadiène) (106-97-8)

LC50 inhalation rat (mg/l)	658 mg/l/4h
----------------------------	-------------

### Ethanol (64-17-5)

LD50 oral	10470 mg/kg bodyweight
-----------	------------------------

LD50 dermal	15800 mg/kg bodyweight
-------------	------------------------

LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 99999 mg/l
---	--------------

Skin corrosion/irritation : Not classified

pH: Not applicable

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified

pH: Not applicable

Respiratory or skin sensitisation : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-repeated exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

### LOFT AMBIANCE WOODY

Product identification	Aerosol
------------------------	---------

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Potential adverse human health effects and symptoms : Long-term exposure at high concentration may cause : brain and nervous system damage. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute aquatic toxicity : Not classified  
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### N-Butane (contenant <0.1% butadiène) (106-97-8)

LC50 fish 1	24.11 mg/l
EC50 Daphnia 1	14.22 mg/l

#### Ethanol (64-17-5)

LC50 fish 1	14200 mg/l
EC50 other aquatic organisms 1	5012 mg/l waterflea
EC50 other aquatic organisms 2	275 mg/l

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

#### N-Butane (contenant <0.1% butadiène) (106-97-8)

Bioaccumulative potential : Not potentially bioaccumulable.

#### Propane (74-98-6)

Bioaccumulative potential : No information available.

#### Ethanol (64-17-5)

Log Pow : -0.32

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose used or damaged aerosol cans at permitted disposal sites. Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.

Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1950	1950	1950	1950	1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

				
---	---	---	---	---

### 14.4. Packing group

Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
----------------	----------------	----------------	----------------	----------------

### 14.5. Environmental hazards

Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
------------------------------------	---	------------------------------------	------------------------------------	------------------------------------

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

No data available

#### Rail transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations : Aerosol Generator Directive 75/324/EEC and its adaptations.

Directive 2012/18/EU (SEVESO III)

#### 15.1.2. National regulations

##### France

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4320.text	Aérosols extrêmement inflammables ou inflammables de catégorie 1 ou 2 contenant des gaz inflammables de catégorie 1 ou 2 ou des liquides inflammables de catégorie 1.		

# LOFT AMBIANCE ONE II

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Imp. DL4.

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Iso E super 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one(54464-57-2), (32210-23-4), ACETYL CEDRENE(32388-55-9), 1-(2,6,6-TRIMETHYL-1,3-CYCLOHEXADIEN-1-YL)-2-BUTEN-1-ONE (BETA-DAMASCENONE)(23696-85-7). May produce an allergic reaction.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*