

**TECHNO CBC**

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : TECHNO CBC  
Product code : 304322/304332/304342.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

Registered company name : IPC S.A.S..  
Address : 10, Quai Commandant Malbert - CS 71821.29218.BREST Cedex 1.France.  
Telephone : +33 (0)2 98 43 45 44. Fax : +33 (0)2 98 44 22 53.  
ipc@ipc-sa.com  
http://www.ipc-sa.com

**1.4. Emergency telephone number : +33 (0)2.98.43.45.44.**

Association/Organisation : .

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).  
Skin corrosion, Category 1A (Skin Corr. 1A, H314).  
Serious eye damage, Category 1 (Eye Dam. 1, H318).  
May produce an allergic reaction (EUH208).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).  
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements**

Detergent mixture (see section 15).

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

EC 231-595-7      HYDROCHLORIC ACID

Additional labeling :

EUH208      Contains METHENAMINE. May produce an allergic reaction.

Hazard statements :

H290      May be corrosive to metals.  
H314      Causes severe skin burns and eye damage.  
H335      May cause respiratory irritation.

Precautionary statements - Prevention :

P264      Wash thoroughly after handling.  
P280      Wear protective gloves/protective clothing/eye protection/face protection.

**TECHNO CBC**

Precautionary statements - Response :

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor/...

P390

Absorb spillage to prevent material damage.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq$  0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 017_002_01_X CAS: 7647-01-0 EC: 231-595-7 REACH: 01-2119484862-27-XXXX  HYDROCHLORIC ACID	GHS05, GHS07 Dgr Met. Corr. 1, H290 Skin Corr. 1B, H314 STOT SE 3, H335	B [1]	10 $\leq$ x % < 25
INDEX: 603_117_00_0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25-XXXX  PROPAN-2-OL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 $\leq$ x % < 2.5
INDEX: 612_101_00_2 CAS: 100-97-0 EC: 202-905-8 REACH: 01-2119474895-20-XXXX  METHENAMINE	GHS07, GHS02 Wng Flam. Sol. 2, H228 Skin Sens. 1, H317		0 $\leq$ x % < 2.5

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures****In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

**In the event of splashes or contact with skin :**

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

**TECHNO CBC**

---

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.  
Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

No data available.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Neutralise with an alkaline decontaminant, such as an aqueous solution of sodium carbonate or similar.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

**TECHNO CBC****6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

**Fire prevention :**

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep the container tightly closed in a dry, well-ventilated place.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
7647-01-0	8	5	15	10	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA	STEL	Ceiling	Definition	Criteria
7647-01-0			2 ppm	A4	
67-63-0	200 ppm	400 ppm		A4; BEI	

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME	VME	Excess	Notes
7647-01-0		2 ppm 3 mg/m <sup>3</sup>		2(I)
67-63-0		200 ppm 500 mg/m <sup>3</sup>		2(II)

- France (INRS - ED984 :2016) :

CAS	VME-ppm	VME-mg/m3	VLE-ppm	VLE-mg/m3	Notes	TMP No
7647-01-0	-	-	5	7.6	-	-
67-63-0	-	-	400	980	-	84

**TECHNO CBC**

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7647-01-0	1 ppm 2 mg/m <sup>3</sup>	5 ppm 8 mg/m <sup>3</sup>			
67-63-0	400 ppm 999 mg/m <sup>3</sup>	500 ppm 1250 mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

METHENAMINE (CAS: 100-97-0)

**Final use:**Exposure method:  
Potential health effects:  
DNEL :**Workers.**Dermal contact.  
Long term systemic effects.  
6.4 mg/kg body weight/dayExposure method:  
Potential health effects:  
DNEL :Inhalation.  
Long term systemic effects.  
5.6 mg of substance/m<sup>3</sup>**Final use:**Exposure method:  
Potential health effects:  
DNEL :**Consumers.**Ingestion.  
Long term systemic effects.  
0.8 mg/kg body weight/dayExposure method:  
Potential health effects:  
DNEL :Dermal contact.  
Long term systemic effects.  
3.2 mg/kg body weight/dayExposure method:  
Potential health effects:  
DNEL :Inhalation.  
Long term systemic effects.  
1.2 mg of substance/m<sup>3</sup>

PROPAN-2-OL (CAS: 67-63-0)

**Final use:**Exposure method:  
Potential health effects:  
DNEL :**Workers.**Dermal contact.  
Long term systemic effects.  
888 mg/kg body weight/dayExposure method:  
Potential health effects:  
DNEL :Inhalation.  
Long term systemic effects.  
500 mg of substance/m<sup>3</sup>**Final use:**Exposure method:  
Potential health effects:  
DNEL :**Consumers.**Ingestion.  
Long term systemic effects.  
26 mg/kg body weight/dayExposure method:  
Potential health effects:  
DNEL :Dermal contact.  
Long term systemic effects.  
319 mg/kg body weight/dayExposure method:  
Potential health effects:  
DNEL :Inhalation.  
Long term systemic effects.  
89 mg of substance/m<sup>3</sup>

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)

**TECHNO CBC****Final use:**

Exposure method:  
Potential health effects:  
DNEL :

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Long term local effects.  
8 mg of substance/m3

Inhalation.  
Short term local effects.  
15 mg of substance/m3

**Predicted no effect concentration (PNEC):****METHENAMINE (CAS: 100-97-0)**

Environmental compartment:  
PNEC : Soil.  
0.28 mg/kg

Environmental compartment:  
PNEC : Fresh water.  
3 mg/l

Environmental compartment:  
PNEC : Sea water.  
0.3 mg/l

Environmental compartment:  
PNEC : Intermittent waste water.  
30 mg/l

Environmental compartment:  
PNEC : Fresh water sediment.  
10.2 mg/kg

Environmental compartment:  
PNEC : Marine sediment.  
1.02 mg/kg

Environmental compartment:  
PNEC : Waste water treatment plant.  
100 mg/l

**PROPAN-2-OL (CAS: 67-63-0)**

Environmental compartment:  
PNEC : Soil.  
28 mg/kg

Environmental compartment:  
PNEC : Fresh water.  
140.9 mg/l

Environmental compartment:  
PNEC : Sea water.  
140.9 mg/l

Environmental compartment:  
PNEC : Intermittent waste water.  
140.9 mg/l

Environmental compartment:  
PNEC : Fresh water sediment.  
552 mg/kg

Environmental compartment:  
PNEC : Waste water treatment plant.  
2251 mg/l

**HYDROCHLORIC ACID ...% (CAS: 7647-01-0)**

Environmental compartment:  
PNEC : Fresh water.  
0.036 mg/l

Environmental compartment:  
Sea water.

**TECHNO CBC**

PNEC :	0.036 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.045 mg/l
Environmental compartment: PNEC :	Marine sediment. 0.045 mg/l
Environmental compartment: PNEC :	Waste water treatment plant. 0.036 mg/l

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- Natural latex

Recommended properties :

- Impervious gloves in accordance with standard EN374

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

**TECHNO CBC**

---

Suitable type of protective boots :

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH :	1.00 +/-1.0. Strongly acidic.
Boiling point/boiling range :	Not specified.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	1.08
Water solubility :	Dilutable.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

**9.2. Other information**

To be translated (XML)

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

Mixture which by chemical action can corrode and even destroy metals.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- frost

**10.5. Incompatible materials**

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)



**TECHNO CBC****SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

**11.1.1. Substances****Acute toxicity :**

METHENAMINE (CAS: 100-97-0)

Oral route : LD50 > 2000 mg/kg  
Species : RatDermal route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 402 (Acute Dermal Toxicity)

PROPAN-2-OL (CAS: 67-63-0)

Oral route : LD50 = 5840 mg/kg  
Species : Rat  
OECD Guideline 401 (Acute Oral Toxicity)Dermal route : LD50 = 13900 mg/kg  
Species : Rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)Inhalation route (n/a) : LC50 > 25 mg/l  
Species : Rat  
OECD Guideline 403 (Acute Inhalation Toxicity)

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)

Oral route : LD50 = 700 mg/kg  
Species : RatDermal route : LD50 > 5010 mg/kg  
Species : RabbitInhalation route (n/a) : LC50 = 45.6 mg/l  
Species : Rat  
Duration of exposure : 4 h**Respiratory or skin sensitisation :**

METHENAMINE (CAS: 100-97-0)

Guinea Pig Maximisation Test (GMPT) : Sensitiser.  
Species : Guinea pig  
OECD Guideline 406 (Skin Sensitisation)

PROPAN-2-OL (CAS: 67-63-0)

Local lymph node stimulation test : Non-Sensitiser.  
Species : Guinea pig  
OECD Guideline 406 (Skin Sensitisation)

**TECHNO CBC**

---

**Germ cell mutagenicity :**

PROPAN-2-OL (CAS: 67-63-0)

Mutagenesis (in vivo) :

Negative.  
Species : Mouse  
OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Mutagenesis (in vitro) :

Negative.  
Species : Bacteria  
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

**Carcinogenicity :**

PROPAN-2-OL (CAS: 67-63-0)

Carcinogenicity Test :

Negative.  
No carcinogenic effect.  
Species : Mouse  
OECD Guideline 451 (Carcinogenicity Studies)

**Reproductive toxicant :**

PROPAN-2-OL (CAS: 67-63-0)

No toxic effect for reproduction

**11.1.2. Mixture**

**Skin corrosion/skin irritation :**

Corrosive classification is based on an extreme pH value.

**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

METHENAMINE (CAS: 100-97-0)

Fish toxicity :

LC50 = 41000 mg/l  
Species : Lepomis macrochirus  
Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 36000 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :

NOEC = 1.5 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 14 days

PROPAN-2-OL (CAS: 67-63-0)

Fish toxicity :

LC50 = 9640 mg/l  
Species : Pimephales promelas  
Duration of exposure : 96 h  
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 = 9714 mg/l  
Species : Daphnia magna  
Duration of exposure : 24 h

**TECHNO CBC**

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 > 100 mg/l  
Species : Raphidocelis subcapitata  
Duration of exposure : 72 h

HYDROCHLORIC ACID ...% (CAS: 7647-01-0)

Fish toxicity :

LC50 = 369 mg/l  
Species : Brachydanio rerio  
Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 213 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :

ECr50 = 0.78 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

**12.2.1. Substances**

METHENAMINE (CAS: 100-97-0)

Biodegradability :

Non-rapidly degradable.

PROPAN-2-OL (CAS: 67-63-0)

Chemical oxygen demand :

DCO = 2.294 g/g

Five-day biochemical oxygen demand :

DBO5 = 1.171 g/g

Biodegradability :

Rapidly degradable.  
DBO5/DCO = 0.51

**12.3. Bioaccumulative potential**

No data available.

**12.3.1. Substances**

METHENAMINE (CAS: 100-97-0)

Octanol/water partition coefficient :

log K<sub>ow</sub> = -2.18  
OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

PROPAN-2-OL (CAS: 67-63-0)

Octanol/water partition coefficient :

log K<sub>ow</sub> = 0.05  
OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**TECHNO CBC****SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2016).

**14.1. UN number**

1789

**14.2. UN proper shipping name**

UN1789=HYDROCHLORIC ACID

**14.3. Transport hazard class(es)**

- Classification :



8

**14.4. Packing group**

II

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C1	II	8	80	1 L	520	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	II	1 L	F-A,S-B	-	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**TECHNO CBC**

---

---

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :**

- less than 5 % : nonionic surfactants

**15.2. Chemical safety assessment**

No data available.

---

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.