

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 10/2/2014 Revision date: 5/15/2019 Supersedes: 12/12/2016 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : TECHNO GALVA BRILLANT
Product code : 307013
Product identification : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Anti-rust, cold galvanizing zinc-based and aluminum ..

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

IPC SAS
10 quai Malbert - CS 71821
29218 BREST CEDEX 2 - FRANCE
T 02-98-43-45-44 - F 02-98-44-22-53 ipc@groupe-ipc.com - www.ipc-sa.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1	H222;H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

butanone; Hydrocarbons, C9, aromatics ; Hydrocarbons C7, n-alkanes, isoalkanes, cyclics

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P211 - Do not spray on an open flame or other ignition source.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection.
P302+P352 - IF ON SKIN: Wash with plenty of water/....
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403 - Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Extra phrases

: For professional use only.
Not to be used for any purpose other than the one the product was designed for.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-Butane (contenant <0.1% butadiène)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	40 - 60	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 20	Flam. Gas 1, H220 Press. Gas (Liq.), H280
butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons C7, n-alkanes, isoalkanes, cyclics	(EC-No.) 927-510-4 (REACH-no) 01-2119475515-33	8 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Xylène	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (REACH-no) 01-21194882216-32	5 - 8	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Zinc en poudre - poussières de zinc (stabilisés)	(CAS-No.) 7440-66-6 (EC-No.) 231-175-3 (REACH-no) 01-2119467174-37	5 - 8	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Xylène (mélanges d'isomères)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (REACH-no) 01-21194882216-32	2 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Hydrocarbures, C9, aromatics	(CAS-No.) 64742-95-6 (EC-No.) 918-668-5 (REACH-no) 01-2119455851-35	0.1 - 0.5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
toluene substance with a Community workplace exposure limit	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	< 0.1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Immediately call a POISON CENTER/doctor. Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Allow the victim to rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties. Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Stinging and temporary redness.
Symptoms/effects after ingestion	: Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Advice to physicians: Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Carbon dioxide. Water spray. Dry powder. AFFF. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Reactivity in case of fire	: Prevent fire fighting water from entering the environment.
Hazardous decomposition products in case of fire	: Incomplete combustion and thermolysis produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water. Exercise caution when fighting any chemical fire. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Ventilate area. Do not smoke. Remove ignition sources. Provide local exhaust or general room ventilation. Evacuate and limit access.
------------------	--

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

Emergency procedures : Do not touch spilled material. Evacuate area.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. Provide adequate ventilation. Remove all sources of ignition. Avoid contact with skin and eyes. Do not inhale vapour.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect the residue by means of a non-combustible absorbent material. Sand. Earth. Vermiculite.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Good ventilation of the workplace required. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck.
During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol.

Hygiene measures

Do not spray the aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in running, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep at temperature not exceeding 50°C. Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.

Storage conditions

: Recommendations applicable to warehouses and reserves which are stored aerosols. It is recommended to de-normalize aerosols in stock . The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock . Do not smoke.

To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).

It is recommended :

- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames
- To use the procedure of fire when working . Store in a dry, well ventilated place .

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

N-Butane (contenant <0.1% butadiène) (106-97-8)

France - Occupational Exposure Limits

Local name	n-Butane
VME (mg/m ³)	1900 mg/m ³
VME (ppm)	800 ppm
Note (FR)	Valeurs recommandées/admises

butanone (78-93-3)

EU - Occupational Exposure Limits

Local name	Butanone
IOELV TWA (mg/m ³)	600 mg/m ³
IOELV TWA (ppm)	200 ppm
IOELV STEL (mg/m ³)	900 mg/m ³
IOELV STEL (ppm)	300 ppm

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

butanone (78-93-3)

France - Occupational Exposure Limits

Local name	Méthyléthylcétone, 2-Butanone
VME (mg/m ³)	600 mg/m ³
VME (ppm)	200 ppm
VLE (mg/m ³)	900 mg/m ³
VLE (ppm)	300 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée

toluene (108-88-3)

EU - Occupational Exposure Limits

Local name	Toluene
IOELV TWA (mg/m ³)	192 mg/m ³
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m ³)	384 mg/m ³
IOELV STEL (ppm)	100 ppm
Notes	skin

France - Occupational Exposure Limits

Local name	Toluène
VME (mg/m ³)	76.8 mg/m ³
VME (ppm)	20 ppm
VLE (mg/m ³)	384 mg/m ³
VLE (ppm)	100 ppm
Note (FR)	Valeurs réglementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2; risque de pénétration percutanée

Hydrocarbons C7, n-alkanes, isoalkanes, cyclics

France - Occupational Exposure Limits

VME (mg/m ³)	1668
VME (ppm)	400 ppm
VLE (mg/m ³)	2085 mg/m ³
VLE (ppm)	500 ppm

8.2. Exposure controls

Hand protection:

Wear suitable gloves resistant to chemical penetration. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer.

Eye protection:

Safety glasses

Skin and body protection:

Skin protection appropriate to the conditions of use should be provided

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Gas mask with filter type A

Other information:

Do not eat, drink or smoke during use. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colour	: dark grey.
Odour	: characteristic.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.88 (PA)
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: < 20.5 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 91.2 % (602 g/l)
-------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

The product is stable at normal handling and storage conditions. Extremely flammable aerosol. Heating may cause a fire or explosion.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Open flame. Heat. Direct sunlight. Sparks. Avoid the build-up of electrostatic charge. Avoid contact with hot surfaces. Remove all sources of ignition.

10.5. Incompatible materials

Strong oxidizers. Aerosol cases in metal, do not bring into contact with oxidize, acids or basis.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

N-Butane (contenant <0.1% butadiène) (106-97-8)

LC50 inhalation rat (mg/l)	658 mg/l/4h
----------------------------	-------------

butanone (78-93-3)

LD50 oral rat	3300 mg/kg
LD50 dermal rabbit	6400 - 8000 mg/kg

Hydrocarbons, C9, aromatics (64742-95-6)

LD50 oral rat	> 4000
LD50 dermal rat	> 2000

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Zinc en poudre - poussières de zinc (stabilisés) (7440-66-6)

LD50 oral rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.4 mg/l/4h

Hydrocarbons C7, n-alkanes, isoalkanes, cyclics

LD50 oral rat	> 5840 mg/kg
LD50 dermal rat	> 2920 mg/kg
LC50 inhalation rat (mg/l)	> 23.3 mg/l/4h

Xylène (1330-20-7)

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 inhalation rat (mg/l)	27124 mg/m ³

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause drowsiness or dizziness.
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: May be fatal if swallowed and enters airways.
Additional information	: Based on available data, the classification criteria are not met

GALVABRILLANT H2

Product identification	Aerosol
Viscosity, kinematic	< 20.5 mm ² /s

Potential adverse human health effects and symptoms	: Eye contact : Stinging and temporary redness. Repeated exposure may cause skin dryness or cracking. Nausea. May be irritating to the mucous membranes and to the respiratory system.
---	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Avoid release to the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.

butanone (78-93-3)

LC50 fish 1	2993 mg/l
EC50 Daphnia 1	308 mg/l

Hydrocarbons, C9, aromatics (64742-95-6)

LC50 fish 1	9.2 mg/l / 96H (Oncorhynchus mykiss - OECD 203)
-------------	---

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 Daphnia 1	3.2 mg/l / 48H (Daphnia magna- OECD 202)
----------------	--

Hydrocarbons C7, n-alkanes, isoalkanes, cyclics

LC50 fish 1	13.4 mg/l 96 H
EC50 Daphnia 2	3 mg/l 48 H

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

N-Butane (contenant <0.1% butadiène) (106-97-8)

Bioaccumulative potential	Not potentially bioaccumulable.
---------------------------	---------------------------------

Propane (74-98-6)

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations






13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose used or damaged aerosol cans at permitted disposal sites. Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 91.2 % (602 g/l)

Other information, restriction and prohibition regulations : Aerosol Generator Directive 75/324/EEC and its adaptations.

15.1.2. National regulations

France

Occupational diseases : RG 4 BIS - Affections gastro-intestinales provoquées par le benzène, le toluène, les xylènes et tous les produits en renfermant
RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4320.text	Aérosols extrêmement inflammables ou inflammables de catégorie 1 ou 2 contenant des gaz inflammables de catégorie 1 ou 2 ou des liquides inflammables de catégorie 1.		

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
9.1	Viscosity, kinematic	Added	
9.2	VOC content	Added	
12.1	Ecology - general	Modified	
15.1	VOC content	Added	

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Imp. DL4.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

TECHNO GALVA BRILLANT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.