

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/10/2014 Revision date: 10/03/2023 Supersedes version of: 24/10/2022 Version: 8.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : TECHNO GALVA MAT
Product code : 307005
Product identification : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Anti-rust, cold galvanizing zinc-based

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

IPC
10 Quai Malbert, 29200, BREST, FRANCE.
Tel. : +33 (0)2 98 43 45 44. Fax : +33 (0)2
98 44 22 53
ipc@groupe-ipc.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 3 H336
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	GHS02	GHS07	GHS09
Signal word (CLP)	: Danger		
Contains	: butanone		
Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H410 - Very toxic to aquatic life with long lasting effects.		
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P391 - Collect spillage. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F. P102 - Keep out of reach of children. P260 - Do not breathe spray. P403 - Store in a well-ventilated place.		
EUH-statements	: EUH208 - Contains Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine. May produce an allergic reaction.		
Extra phrases	: For professional use only. Not to be used for any purpose other than the one the product was designed for. Seek medical attention if ill effect develops.		

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-Butane (contenant <0.1% butadiène) (Propellant gas (Aerosol))	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	30 – 40	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
butanone substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	15 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	10 – 20	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
zinc powder— zinc dust (stabilised)	CAS-No.: 7440-66-6 EC-No.: 231-175-3 EC Index-No.: 030-001-01-9 REACH-no: 01-2119467174-37	10 – 20	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylene (mixtures of isomers) substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-21194882216-32	2 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg) Acute Tox. 4 (Inhalation:vapour), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Hydrocarbons C7, n-alkanes, isoalkanes, cyclics substance with national workplace exposure limit(s) (FR)	EC-No.: 927-510-4 REACH-no: 01-2119475515-33	2 – 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9, aromatics	EC-No.: 918-668-5 REACH-no: 01-2119455851-35	1 – 2	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylbenzene substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	0.5 – 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304
ethylbenzene substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	0.5 – 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
ethanol substance with national workplace exposure limit(s) (FR)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	0.1 – 0.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine	EC-No.: 434-430-9 REACH-no: 01-0000018057-71	0.1 – 0.5	Skin Sens. 1B, H317 STOT RE 2, H373 Aquatic Chronic 4, H413

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
toluene substance with national workplace exposure limit(s) (FR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	< 0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
2-methylpropan-1-ol substance with national workplace exposure limit(s) (FR)	CAS-No.: 78-83-1 EC-No.: 201-148-0 EC Index-No.: 603-108-00-1 REACH-no: 01-2119484609-23	< 0.1	Flam. Liq. 3, H226 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	(50 ≤C < 100) Eye Irrit. 2, H319

Comments : Calculation of aerosol labeling excluding gas
Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell. If you feel unwell, seek medical advice.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Allow the victim to rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Reactivity in case of fire : Prevent fire fighting water from entering the environment.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Ventilate area. Do not smoke. Remove ignition sources. Provide local exhaust or general room ventilation. Evacuate and limit access. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Do not touch spilled material. Evacuate area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Provide adequate ventilation. Do not inhale vapour.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product. Clean spills promptly. Collect the residue by means of a non-combustible absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck.
During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol.
Do not spray tha aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in runing, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Recommendations applicable to warehouses and reserves which are stored aerosols.
It is recommended to de-normalize aerosols in stock . The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock . Do not smoke.
- To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).
It is recommended :
- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames
- To use the procedure of fire when working . Store in a dry, well ventilated place .

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butanone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Butanone
IOEL TWA	600 mg/m ³
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m ³
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA	442 mg/m ³
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m ³
IOEL STEL [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Xylene (mixtures of isomers) (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA	192 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	384 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA	442 mg/m ³
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m ³
IOEL STEL [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
N-Butane (contenant <0.1% butadiène) (106-97-8)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1450 mg/m ³

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

N-Butane (contenant <0.1% butadiène) (106-97-8)	
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
WEL STEL (OEL STEL) [ppm]	750 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Skin protection appropriate to the conditions of use should be provided

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: dark grey.
Odour	: Not available

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated. Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: < 20.5 mm ² /s (PA 40°C)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.1 (PA)
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 84 %

9.2.2. Other safety characteristics

VOC content : 603.7 g/l (82.5 %)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Extremely high or low temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone (78-93-3)	
LD50 oral	2193
Hydrocarbons C7, n-alkanes, isoalkanes, cyclics	
LD50 oral rat	> 5840 mg/kg
LD50 dermal rat	> 2920 mg/kg
LC50 Inhalation - Rat	> 23.3 mg/l/4h
zinc powder— zinc dust (stabilised) (7440-66-6)	
LD50 oral rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.4 mg/l/4h
Xylene (mixtures of isomers) (1330-20-7)	
LD50 oral	3523 mg/kg
LD50 dermal	12126 mg/kg
LC50 Inhalation - Rat	27124 mg/l
Hydrocarbons, C9, aromatics	
LD50 oral	3592 mg/kg
LD50 dermal	> 3160 mg/kg
Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine	
LD50 oral rat	2000 mg/kg
LD50 dermal rat	2000 mg/kg
LC50 Inhalation - Rat	4.1 mg/l/4h
ethanol (64-17-5)	
LD50 oral	10470 mg/kg
LD50 dermal	15800 mg/kg
LC50 Inhalation - Rat	50000 mg/m ³
2-methylpropan-1-ol (78-83-1)	
LD50 oral	3350 mg/kg
LD50 dermal	2460 mg/kg
LC50 Inhalation - Rat	18200 mg/m ³
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 Inhalation - Rat	17.6 mg/l

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons C7, n-alkanes, isoalkanes, cyclics	
STOT-single exposure	May cause drowsiness or dizziness.
Xylene (mixtures of isomers) (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
Hydrocarbons, C9, aromatics	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
2-methylpropan-1-ol (78-83-1)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
Xylene (mixtures of isomers) (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
TECHNO GALVA MAT	
Product identification	Aerosol
Viscosity, kinematic	< 20.5 mm ² /s (PA 40°C)

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Eye contact :Stinging and temporary redness,Repeated exposure may cause skin dryness or cracking,May be irritating to the mucous membranes and to the respiratory system,Nausea

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.

butanone (78-93-3)	
LC50 - Fish [1]	2993 mg/l
EC50 - Crustacea [1]	308 mg/l
Hydrocarbons C7, n-alkanes, isoalkanes, cyclics	
LC50 - Fish [1]	13.4 mg/l
EC50 - Crustacea [1]	3 mg/l
Xylene (mixtures of isomers) (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l
EC50 - Crustacea [1]	1 mg/l
EC50 72h - Algae [1]	2.2 mg/l
Hydrocarbons, C9, aromatics	
LC50 - Fish [1]	9.2 mg/l <i>Oncorhynchus mykiss</i>
EC50 - Crustacea [1]	21.3 mg/l <i>Daphnia magna</i>
ethanol (64-17-5)	
LC50 - Fish [1]	11200 mg/l
LC50 - Fish [2]	13000 mg/l
EC50 - Crustacea [1]	12340 mg/l
EC50 72h - Algae [1]	275 mg/l
toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l
EC50 - Crustacea [1]	3.78 mg/l
EC50 72h - Algae [1]	134 mg/l
2-methylpropan-1-ol (78-83-1)	
LC50 - Fish [1]	1430 mg/l
EC50 - Crustacea [1]	1100 mg/l
EC50 72h - Algae [1]	1799 mg/l
ethylbenzene (100-41-4)	
LC50 - Fish [1]	4.2 mg/l
EC50 - Crustacea [1]	1.8 mg/l
EC50 72h - Algae [1]	7.7 mg/l

12.2. Persistence and degradability

butanone (78-93-3)	
Persistence and degradability	Readily biodegradable.
Hydrocarbons C7, n-alkanes, isoalkanes, cyclics	
Persistence and degradability	Readily biodegradable.
Biodegradation	98 %

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Xylene (mixtures of isomers) (1330-20-7)	
Persistence and degradability	Readily biodegradable.
Biodegradation	> 60 %
Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine	
Biodegradation	6 %
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
2-methylpropan-1-ol (78-83-1)	
Persistence and degradability	Readily biodegradable.
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.
N-Butane (contenant <0.1% butadiène) (106-97-8)	
Persistence and degradability	Half-life time in water: <2.6 d Half-life time in air: 3.2 d.
propane (74-98-6)	
Biodegradation	< 60 % 28d

12.3. Bioaccumulative potential

ethylbenzene (100-41-4)	
Partition coefficient n-octanol/water (Log Pow)	3.15
N-Butane (contenant <0.1% butadiène) (106-97-8)	
Bioaccumulative potential	Not potentially bioaccumulable.
propane (74-98-6)	
Bioaccumulative potential	No information available.

12.4. Mobility in soil

ethylbenzene (100-41-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.72

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Ecology - waste materials	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Aerosol Generator Directive 75/324/EEC and its adaptations.

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	GALVAMAT ; butanone ; ethylbenzene ; Hydrocarbons C7, n-alkanes, isoalkanes, cyclics ; Xylene (mixtures of isomers) ; Hydrocarbons, C9, aromatics ; ethanol ; toluene ; 2-methylpropan-1-ol ; ethylbenzene
3(b)	GALVAMAT ; butanone ; ethylbenzene ; Hydrocarbons C7, n-alkanes, isoalkanes, cyclics ; Xylene (mixtures of isomers) ; Hydrocarbons, C9, aromatics ; Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine ; ethanol ; toluene ; 2-methylpropan-1-ol ; ethylbenzene
3(c)	GALVAMAT ; Hydrocarbons C7, n-alkanes, isoalkanes, cyclics ; Xylene (mixtures of isomers) ; Hydrocarbons, C9, aromatics ; Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine ; toluene ; ethylbenzene
40.	butanone ; ethylbenzene ; Hydrocarbons C7, n-alkanes, isoalkanes, cyclics ; Xylene (mixtures of isomers) ; Hydrocarbons, C9, aromatics ; ethanol ; toluene ; 2-methylpropan-1-ol ; ethylbenzene ; N-Butane (contenant <0.1% butadiène) ; propane
48.	toluene

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 603.7 g/l (82.5 %)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
	Flammability (solid, gas)	Added	
2.1	Adverse physicochemical, human health and environmental effects	Added	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Extra phrases	Added	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after inhalation	Added	
4.1	First-aid measures after ingestion	Added	
4.1	First-aid measures after eye contact	Added	

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
4.1	First-aid measures after skin contact	Added	
4.1	First-aid measures general	Added	
4.2	Symptoms/effects after ingestion	Added	
4.2	Symptoms/effects after eye contact	Added	
4.2	Symptoms/effects after skin contact	Added	
4.2	Symptoms/effects	Added	
4.3	Other medical advice or treatment	Added	
5.1	Unsuitable extinguishing media	Added	
5.1	Suitable extinguishing media	Added	
5.2	Reactivity in case of fire	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.2	Fire hazard	Added	
5.2	Explosion hazard	Added	
5.3	Firefighting instructions	Added	
5.3	Protection during firefighting	Added	
6.1	Emergency procedures	Added	
6.1	General measures	Added	
6.1	Protective equipment	Added	
6.1	Emergency procedures	Added	
6.2	Environmental precautions	Added	
6.3	Other information	Added	
6.3	For containment	Added	
6.3	Methods for cleaning up	Added	
6.4	Reference to other sections (8, 13)	Added	
7.1	Hygiene measures	Added	
7.1	Precautions for safe handling	Added	
7.2	Technical measures	Added	
7.2	Storage conditions	Added	
8.2	Environmental exposure controls	Added	
8.2	Respiratory protection	Added	
8.2	Hand protection	Added	
8.2	Eye protection	Added	
8.2	Appropriate engineering controls	Added	
8.2	Skin and body protection	Added	
9.1	Melting point	Added	
9.1	Explosive properties	Modified	
9.1	Relative density	Modified	

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
9.2	VOC content	Modified	
10.1	Reactivity	Added	
10.2	Chemical stability	Added	
10.3	Possibility of hazardous reactions	Added	
10.4	Conditions to avoid	Added	
10.5	Incompatible materials	Added	
10.6	Hazardous decomposition products	Added	
12.1	Ecology - general	Added	
13.1	Waste disposal recommendations	Added	
13.1	Ecology - waste materials	Added	
13.1	Waste treatment methods	Added	
15.1	REACH Annex XVII	Added	
15.1	VOC content	Modified	
16	Abbreviations and acronyms	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Other information : Imp. DL4.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.

TECHNO GALVA MAT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.