SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : TORNADE BIOTECH AD 2D MENTHE Product code : 104230.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent.

Professional use.

1.3. Details of the supplier of the safety data sheet

IPC

10 Quai Malbert, 29200, BREST, FRANCE. Tel. : +33 (0)2 98 43 45 44. Fax : +33 (0)2 98 44 22 53 ipc@groupe-ipc.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).

Skin corrosion, Category 1C (Skin Corr. 1C, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :





GHS05
L-(+)-LACTIC ACID
5 D-GLUCITOL, 1-DEOXY-1-(METHYLAMINO)-, N-C8-10 ACYL DERIVS.
GLYCOLIC ACID
SULPHURIC ACID ESTERS OF MONO-ALKYL C12-16, SODIUM SALTS
g :
Contains L-CARVONE. May produce an allergic reaction.
:
Flammable liquid and vapour.
May be corrosive to metals.
Causes severe skin burns and eye damage.
ements - Prevention :
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep only in original packaging.

E BIOTECH AD 2D MENTHE		
		-

Date : 16/03/2023 Page 2/19

Revision : N°1 (16/03/2023)

P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER, a doctor.
P390	Absorb spillage to prevent material damage.
Precautionary statements - Disposal :	
P501	Dispose of contents/container in accordance with local / regional / national / international regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances > = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Composition :	1		
Identification	(EC) 1272/2008	Note	%
INDEX: 607-743-00-5	GHS05		$10 \le x \% \le 25$
CAS: 79-33-4	Dgr		
EC: 201-196-2	Skin Corr. 1C, H314		
	Eye Dam. 1, H318		
L-(+)-LACTIC ACID	EUH:071		
INDEX: 603 002 00 5	GHS07, GHS02	[1]	$10 \le x \% \le 25$
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43	Eye Irrit. 2, H319		
ETHANOL			
INDEX: E422		[1]	$2.5 \le x \% \le 10$
CAS: 56-81-5			
EC: 200-289-5			
GLYCEROL			
INDEX: 68515_73_1	GHS05		$2.5 \le x \% \le 10$
CAS: 68515-73-1	Dgr		
EC: 500-220-1	Eye Dam. 1, H318		
REACH: 01-2119488530-36			
D-GLUCOPYRANOSE, OLIGOMÉRIQUES,			
DÉCYL OCTYL GLYCOSIDES			
INDEX: 1591782_62_5	GHS07, GHS05		$2.5 \le x \% \le 10$
CAS: 1591782-62-5	Dgr		
REACH: 01-2120028964-50	Eye Dam. 1, H318		
	Acute Tox. 4, H332		
D-GLUCITOL,			
1-DEOXY-1-(METHYLAMINO)-, N-C8-10			
ACYL DERIVS.			
INDEX: 79_14_1	GHS07, GHS05		$1 \le x \% \le 2.5$
CAS: 79-14-1	Dgr		
EC: 201-180-5	Met. Corr. 1, H290		
REACH: 01-2119485579-17	Skin Corr. 1B, H314		
	Acute Tox. 4, H332		
GLYCOLIC ACID			

INDEX: 73296_89_6	GHS05		$1 \le x \% < 2.5$
CAS: 73296-89-6	Dgr		
EC: 277-362-3	Skin Irrit. 2, H315		
REACH: 01-2119489464-26	Eye Dam. 1, H318		
	Aquatic Chronic 3, H412		
SULDIUDICACIDESTEDS OF	Aquatic Chronic 5, H412		
SULPHURIC ACID ESTERS OF			
MONO-ALKYL C12-16, SODIUM SALTS			
INDEX: 110_44_1	GHS07		$1 \le x \% < 2.5$
CAS: 110-44-1	Wng		
EC: 203-768-7	Skin Irrit. 2, H315		
REACH: 01-2119950330-49	Eye Irrit. 2, H319		
	STOT SE 3, H335		
LIEVA 24 DIENOIC ACID	5101 52 5, 11555		
HEXA-2,4-DIENOIC ACID		[1]	0.1 < 0/ < 1
INDEX: 57_55_6		[1]	0.1 <= x % < 1
CAS: 57-55-6			
EC: 200-338-0			
REACH: 01-2119456809-23			
PROPYLENE GLYCOL			
INDEX: I6485 40 1	GHS07		$0.1 \le x \% \le 1$
CAS: 6485-40-1			\vee \wedge \wedge \vee \wedge \vee \wedge
	Wng		
EC: 229-352-5	Skin Sens. 1B, H317		
REACH: 01-2119962458-25			
L-CARVONE			
INDEX: I601029007A	GHS02, GHS07, GHS08, GHS09	[1]	$0 \le x \% < 0.1$
CAS: 5989-27-5	Dgr		
EC: 227-813-5	Flam. Liq. 3, H226		
REACH: 01-2119529223-47	Asp. Tox. 1, H304		
	Skin Irrit. 2, H315		
D-LIMONENE	Skin Sens. 1B, H317		
	Aquatic Chronic 3, H412		
	Aquatic Acute 1, H400		
	MAcute = 1		
INDEX: 80 56 8B	GHS07, GHS09, GHS08, GHS02	[1]	$0 \le x \% \le 0.1$
CAS: 80-56-8	Dgr		0 ~ x /0 ~ 0.1
EC: 201-291-9	Flam. Liq. 3, H226		
REACH: 01-2119519223-49	Asp. Tox. 1, H304		
	Skin Irrit. 2, H315		
ALPHA-PINENE	Skin Sens. 1B, H317		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
NIDEY, 1127, 01, 2	M Chronic = 1	Γ1	0 < 0 < - 0.1
INDEX: 1127_91_3	GHS02, GHS07, GHS08, GHS09	[1]	$0 \le x \% < 0.1$
CAS: 127-91-3	Dgr		
EC: 204-872-5	Flam. Liq. 3, H226		
REACH: 01-2119519230-54	Asp. Tox. 1, H304		
	Skin Irrit. 2, H315		
BETA-PINENE	Skin Sens. 1B, H317		
	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		
Specific concentration limits:			
Identification	Specific concentration limits	ATE	
INDEX: 603 002 00 5	Eye Irrit. 2A: H319 C>= 50%	ATE inhalation: ATE = 5	1 mg/1 /h
	Bye IIII. 2A. H519 C/- 5070	Initiation ALE = 3	1 111g/1 4 11
CAS: 64-17-5		1	// DV:
EC: 200-578-6		oral: ATE = 10470 1	ng/kg BW
REACH: 01-2119457610-43			
ETHANOL			

INDEX: 1591782_62_5		oral: ATE = 500 mg/kg BW
CAS: 1591782-62-5		
REACH: 01-2120028964-50		
D-GLUCITOL,		
1-DEOXY-1-(METHYLAMINO)-, N-C8-10		
ACYL DERIVS.		
INDEX: 79 14 1		dermal: $ATE = 3.6 \text{ mg/kg BW}$
CAS: 79-14-1		oral: ATE = 2040 mg/kg BW
EC: 201-180-5		
REACH: 01-2119485579-17		
GLYCOLIC ACID		
INDEX: 73296 89 6	Eye Dam. 1: H318 C>= 20%	
CAS: 73296-89-6	Eye Irrit. 2: H319 10% <= C < 20%	
EC: 277-362-3		
REACH: 01-2119489464-26		
SULPHURIC ACID ESTERS OF		
MONO-ALKYL C12-16, SODIUM SALTS		
INDEX: I6485 40 1		dermal: ATE = 3800 mg/kg BW
CAS: 6485-40-1		oral: ATE = 2500 mg/kg BW
EC: 229-352-5		
REACH: 01-2119962458-25		
L-CARVONE		
INDEX: 80_56_8B		oral: ATE = 3500 mg/kg BW
CAS: 80-56-8		
EC: 201-291-9		
REACH: 01-2119519223-49		
ALPHA-PINENE		

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of massive inhalation, remove the person to fresh air and keep warm and at rest.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital. In case of skin contact, rinse with plenty of water for at least 15 minutes. Contact a doctor.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an alkaline decontaminant, such as an aqueous solution of sodium carbonate or similar.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep out of reach of children.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Recommended storage temperature: + $5^{\circ}C$ to + $40^{\circ}C$

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- Germany - AGW (BAuA - TRGS 900, 02/2022) :				
CAS	VME :	VME :	Excess	Notes
64-17-5		200 ppm		4(II)
		380 mg/m ³		
56-81-5		200 E mg/m ³		2 (I)
5989-27-5		5 ppm		4(II)
		28 mg/m ³		

- Belgium (Royal decree of 11/05/2021) :

CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm				
	1907 mg/m ³				
56-81-5	10 mg/m ³				

		-		1	-	
80-56-8	20 ppm					
127-91-3	20 ppm					
- France (INRS	- Outils 65 / 2021-	1849, 2021-176	3, decree of 09/1	12/2021):		
CAS	VME-ppm :	VME-mg/m3	: VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84
56-81-5	-	10	-	-	-	-
- Switzerland (S	Suva 2021) :					
CAS	VMÉ	VLE	Valeur plafond	Notations		
64-17-5	500 ppm	1000 ppm				
	960 mg/m ³	1920 mg/m ³				
56-81-5	50 ppm	100 ppm				
5989-27-5	7 ppm	14 ppm				
	40 mg/m ³	80 mg/m ³				
- UK / WEL (W	orkplace exposure	limits, EH40/20	05, Fourth Editi	on 2020) :		
CAS	TWA:	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5	1000 ppm					
	1920 mg/m ³					
56-81-5	10 mg/m ³					
57-55-6	10 mg/m ³					
Derived no effect	t level (DNEL) or o	lerived minimu	m effect level (DMEL):		
HEXA-2,4-1	DIENOIC ACID (C	CAS: 110-44-1)				
Final use:	· ·	,	Worker	'S.		
Exposure method: Dermal contact.						
Potential health effects:		Long term	systemic effect	s.		
DNEL :		40 mg/kg body weight/day				
Exposure			Inhalation.			
Potential	Potential health effects:			systemic effect		
DNEL :			17.63 mg c	of substance/m3	;	

Consumers.

Ingestion. Long term systemic effects. 2 mg/kg body weight/day

Dermal contact. Long term systemic effects. 20 mg/kg body weight/day

Dermal contact. Long term local effects. 0.17 mg of substance/cm2

Inhalation. Long term systemic effects. 52.17 mg of substance/m3

Inhalation. Long term local effects. 26.08 mg of substance/m3

SULPHURIC ACID ESTERS OF MONO-ALKYL C12-16, SODIUM SALTS (CAS: 73296-89-6)

Final use: Exposure method: Potential health effects: DNEL:

Exposure method:

Final use:

DNEL :

DNEL :

DNEL :

DNEL :

DNEL :

Exposure method:

Exposure method:

Exposure method:

Exposure method:

Exposure method:

Potential health effects:

Workers. Dermal contact. Long term systemic effects. 4060 mg/kg body weight/day

Inhalation.

Date : 16/03/2023 Page 8/19 Revision : N°1 (16/03/2023)

Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

GLYCOLIC ACID (CAS: 79-14-1)

Final use: Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects:

DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: Long term systemic effects. 285 mg of substance/m3

Consumers. Ingestion. Long term systemic effects. 24 mg/kg body weight/day

Dermal contact. Long term systemic effects. 2440 mg/kg body weight/day

Inhalation. Long term systemic effects. 85 mg of substance/m3

Workers. Dermal contact. Long term systemic effects. 57.69 mg/kg body weight/day

Inhalation. Short term systemic effects. 9.2 mg of substance/m3

Inhalation. Short term local effects. 9.2 mg of substance/m3

Inhalation. Long term systemic effects. 10.56 mg of substance/m3

Inhalation. Long term local effects. 1.53 mg of substance/m3

Consumers. Ingestion. Long term systemic effects. 0.75 mg/kg body weight/day

Dermal contact. Short term local effects. 28.85 mg/kg body weight/day

Inhalation. Short term systemic effects. 2.3 mg of substance/m3

Inhalation. Short term local effects. 2.3 mg of substance/m3

Inhalation. Long term systemic effects.

DNEL:

2.6 mg of substance/m3

D-GLUCITOL, 1-DEOXY-1-(METHYLAMINO)-, N-C8-10 ACYL DERIVS. (CAS: 1591782-62-5)

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL:

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Final use:

Exposure method: Potential health effects: DNEL:

Exposure method: Potential health effects: DNEL:

Exposure method: Potential health effects: DNEL :

ETHANOL (CAS: 64-17-5) Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL:

Workers. Dermal contact. Long term systemic effects. 30 mg/kg body weight/day

Inhalation. Long term systemic effects. 10.58 mg of substance/m3

Consumers. Ingestion. Long term systemic effects. 2.14 mg/kg body weight/day

Dermal contact. Long term systemic effects. 21.43 mg/kg body weight/day

Inhalation. Long term systemic effects. 3.73 mg of substance/m3

D-GLUCOPYRANOSE, OLIGOMÉRIQUES, DÉCYL OCTYL GLYCOSIDES (CAS: 68515-73-1)

Workers. Dermal contact. Long term systemic effects. 595000 mg/kg body weight/day

Inhalation. Long term systemic effects. 420 mg of substance/m3

Consumers.

Ingestion. Long term systemic effects. 35,7 mg/kg body weight/day

Dermal contact. Long term systemic effects. 357000 mg/kg body weight/day

Inhalation. Long term systemic effects. 124 mg of substance/m3

Workers. Dermal contact. Long term systemic effects. 343 mg/kg body weight/day

Inhalation. Short term local effects. 1900 mg of substance/m3

Exposure method: Potential health effects: DNEL :

Final use:

Exposure method: Potential health effects: DNEL :

Predicted no effect concentration (PNEC):

P]	ROPYLENE GLYCOL (CAS: 57-55-6) Environmental compartment:	Soil.
	PNEC :	50 mg/kg
	Environmental compartment: PNEC :	Fresh water. 206 mg/l
	Environmental compartment: PNEC :	Sea water. 26 mg/l
H	EXA-2,4-DIENOIC ACID (CAS: 110-44-1) Environmental compartment: PNEC :	Soil. 5 mg/kg
	Environmental compartment: PNEC :	Fresh water. 0.129 mg/l
	Environmental compartment: PNEC :	Fresh water sediment. 0.465 mg/kg
	Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l
SI	ULPHURIC ACID ESTERS OF MONO-ALKYL Environmental compartment: PNEC :	C12-16, SODIUM SALTS (CAS: 73296-89-6) Soil. 0.616 mg/kg
	Environmental compartment: PNEC :	Fresh water. 0.096 mg/l
	Environmental compartment: PNEC :	Sea water. 0.0096 mg/l
	Environmental compartment: PNEC :	Intermittent waste water. 0.036 mg/l
	Environmental compartment:	Fresh water sediment.

Inhalation. Long term systemic effects. 950 mg of substance/m3

Consumers. Ingestion. Short term systemic effects. 87 mg/kg body weight/day

Dermal contact. Long term systemic effects. 206 mg/kg body weight/day

Inhalation. Short term local effects. 950 mg of substance/m3

Inhalation. Long term systemic effects. 114 mg of substance/m3

PNEC :	3.37 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.337 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	1084 mg/l
GLYCOLIC ACID (CAS: 79-14-1) Environmental compartment: PNEC :	Soil. 0.007 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.0321 mg/l
Environmental compartment:	Sea water.
PNEC :	0.0031 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.312 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.115 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.0155 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	7 mg/l
D-GLUCITOL, 1-DEOXY-1-(METHYLAMINO)-, N-C8-10 ACYL DERIVS. (CAS: 1591782-62-5)
Environmental compartment:	Soil.
PNEC :	36.6 mg/kg
Environmental compartment:	Fresh water.
PNEC :	10 mg/l
Environmental compartment:	Sea water.
PNEC :	1 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	50 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	94 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	9.4 mg/kg
D-GLUCOPYRANOSE, OLIGOMÉRIQUES, D	ÉCYL OCTYL GLYCOSIDES (CAS: 68515-73-1)
Environmental compartment:	Soil.
PNEC :	0,654 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.176 mg/l
Environmental compartment:	Sea water.
PNEC :	0.0176 mg/l
Environmental compartment:	Intermittent waste water.

PNEC :	0.27 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	1,516 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0,152 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	560 mg/l
ETHANOL (CAS: 64-17-5) Environmental compartment: PNEC :	Soil. 0.63 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.96 mg/l
Environmental compartment:	Sea water.
PNEC :	0.79 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	2.75 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	3.6 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	2.9 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	580 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Suitable type of protective boots :

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	
Physical state :	Fluid liquid.
Colour	
Colorless to pale yellow	
Odour	
Odour threshold :	Not stated.
Mint	
Melting point	
Melting point/melting range :	Not specified.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling range	
Boiling point/boiling range :	Not specified.
Flammability	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%) :	Not stated.
Flash point	
Flash Point Interval :	$23^{\circ}C \le FP \le 55^{\circ}C$
Auto-ignition temperature	
Self-ignition temperature :	Not specified.
Decomposition temperature	
Decomposition point/decomposition range :	Not specified.
рН	
pH:	2.15 .
	Slightly acidic.
pH (aqueous solution) :	Not stated.
Kinematic viscosity	
Viscosity :	Not stated.
Solubility	
Water solubility :	Soluble.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
	Not relevant.
Vapour pressure (50°C) :	INOUTCICVAIII.
Vapour pressure (50°C) : Density and/or relative density	Not relevant.

Not stated.

Method for determining the density : ISO 649-2 (Laboratory glassware - Density hydrometers for general purposes - Part 2: Test methods and use).

Relative vapour density

Vapour density :

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

Mixture which by chemical action can corrode and even destroy metals.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.

- heating
- heat
- flames and hot surfaces

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between one and four hours.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

11.1.1. Substances

Acute toxicity :

ALPHA-PINENE (CAS: 80-56-8) Oral route :	LD50 = 3500 mg/kg
L-CARVONE (CAS: 6485-40-1) Oral route :	LD50 = 2500 mg/kg
Dermal route :	LD50 = 3800 mg/kg
PROPYLENE GLYCOL (CAS: 57-55-6) Oral route :	LD50 > 5000 mg/kg Species : Rat
Dermal route :	LD50 > 2000 mg/kg

	Species : Rabbit
HEXA-2,4-DIENOIC ACID (CAS: 110-44-1) Oral route :	LD50 > 10000 mg/kg Species : Rat
Dermal route :	LD50 > 2000 mg/kg Species : Rat
GLYCOLIC ACID (CAS: 79-14-1) Oral route :	LD50 = 2040 mg/kg Species : Rat
Dermal route :	LD50 = 3.6 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 > 5.2 mg/l Species : Rat
D-GLUCITOL, 1-DEOXY-1-(METHYLAMINO Oral route :)-, N-C8-10 ACYL DERIVS. (CAS: 1591782-62-5) LD50 = 500 mg/kg Species : Rat OECD Guideline 423 (Acute Oral toxicityAcute Toxic Class Method)
Dermal route :	LD50 > 2000 mg/kg Species : Rat OECD Guideline 402 (Acute Dermal Toxicity)
Inhalation route (Dusts/mist) :	LC50 5 mg/l Species : Rat OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method) Duration of exposure : 4 h
D-GLUCOPYRANOSE, OLIGOMÉRIQUES, D Oral route :	ÉCYL OCTYL GLYCOSIDES (CAS: 68515-73-1) LD50 <= 5000 mg/kg Species : Rat OECD Guideline 401 (Acute Oral Toxicity)
Dermal route :	LD50 > 2000 mg/kg Species : Rabbit OECD Guideline 402 (Acute Dermal Toxicity)
ETHANOL (CAS: 64-17-5) Oral route :	LD50 = 10470 mg/kg Species : Rat OECD Guideline 401 (Acute Oral Toxicity)
Dermal route :	LD50 > 2000 mg/kg Species : Rabbit OECD Guideline 402 (Acute Dermal Toxicity)
Inhalation route (n/a) :	LC50 = 51 mg/l Species : Rat Duration of exposure : 4 h
1.2 Mixture	

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards

SECTION 12 : ECOLOGICAL INFORMATION	
12.1. Toxicity	
12.1.1. Substances	
HEXA-2,4-DIENOIC ACID (CAS: 110-44-1)	
Fish toxicity :	LC50 = 1250 mg/l Species : Brachydanio rerio Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 = 353 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 = 24.1 mg/l Species : Scenedesmus subspicatus Duration of exposure : 72 h
Aquatic plant toxicity :	Species : Others Duration of exposure : 72 h
D-GLUCITOL, 1-DEOXY-1-(METHYLAMINO) Fish toxicity :	-, N-C8-10 ACYL DERIVS. (CAS: 1591782-62-5) LC50 > 100 mg/l Species : Danio rerio Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
D-GLUCOPYRANOSE, OLIGOMÉRIQUES, DÉ Fish toxicity :	CYL OCTYL GLYCOSIDES (CAS: 68515-73-1) LC50 > 100 mg/l Species : Brachydanio rerio Duration of exposure : 96 h

NOEC > 1 mg/l Species : Brachydanio rerio

Crustacean toxicity :

EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 48 h

NOEC > 1 mg/l Species : Daphnia magna

LC50 = 13000 mg/l

ETHANOL (CAS: 64-17-5) Fish toxicity :

Crustacean toxicity :

OECD Guideline 203 (Fish, Acute Toxicity Test) EC50 = 5012 mg/l

Species : Ceriodaphnia dubia

Species : Oncorhynchus mykiss Duration of exposure : 96 h

Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of Member States and will be provided with their request or at the request of a detergent manufacturer.

12.2.1. Substances PROPYLENE GLYCOL (CAS: 57-55-6) Biodegradability : Rapidly degradable. HEXA-2,4-DIENOIC ACID (CAS: 110-44-1) Biodegradability : Rapidly degradable. SULPHURIC ACID ESTERS OF MONO-ALKYL C12-16, SODIUM SALTS (CAS: 73296-89-6) Biodegradability : Rapidly degradable. GLYCOLIC ACID (CAS: 79-14-1) Biodegradability : Rapidly degradable. D-GLUCITOL, 1-DEOXY-1-(METHYLAMINO)-, N-C8-10 ACYL DERIVS. (CAS: 1591782-62-5) Biodegradability : Rapidly degradable. D-GLUCOPYRANOSE, OLIGOMÉRIQUES, DÉCYL OCTYL GLYCOSIDES (CAS: 68515-73-1) Biodegradability : Rapidly degradable. ETHANOL (CAS: 64-17-5) Biodegradability : Rapidly degradable. 12.3. Bioaccumulative potential No data available. 12.4. Mobility in soil No data available. 12.5. Results of PBT and vPvB assessment No data available. 12.6. Endocrine disrupting properties No data available. 12.7. Other adverse effects No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

2924

14.2. UN proper shipping name

UN2924=FLAMMABLE LIQUID, CORROSIVE, N.O.S.

(ethanol, l-(+)-lactic acid)

14.3. Transport hazard class(es)

- Classification :



3+8

14.4. Packing group

III

14.5. Environmental hazards

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	FC	III	3+8	38	5 L	274	E1	3	D/E
										_
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	3	8	III	5 L	F-E. S-C	223 274	E1	Category A SW2	-	
	•	•	•			•				

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	8	III	354	5 L	365	60 L	A3 A803	E1
	3	8	III	Y342	1 L	-	-	A3 A803	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

- Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : anionic surfactants

- 5 % or over but less than 15 % : non-ionic surfactants
- perfumes
- preservatives
- sorbic acid
- potassium sorbate
- allergenic fragrances :
- d-limonene

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS05 : Corrosion

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.